



[Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062](#)


## Suzuki GSX-R1000 (07-08) PAIR Block-Off Cap Installation Instructions

The black cap included with your exhaust system purchase is used to block off the flow of fresh air into the exhaust system preventing 'deceleration pop'. Blocking of the PAIR system is also required for proper fuel tuning of the bike.

*For additional installation support please refer to the OEM service manual.*

### Installation Instructions:

1. Lift and prop the gas tank.
2. Remove the PAIR hose from the nipple located on the right front of the airbox (Fig 1).
3. Place the supplied black cap over the nipple (Fig 2).
4. Reinstall the PAIR hose over the cap (lubricate the cap with WD-40 to ease installation) and reinstall hose clamp (Fig 3).
5. Reinstall the fuel tank.



**ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!**

For more information on Brock's Performance Warranty and Terms and Conditions:

**[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Terms and Conditions](#)**

For Questions and Comments:

**[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Contact us](#) or call 937-912-0054**