

Brock's PERFORMANCE

Brock's Performance Products • 4064 East Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

Installation Instructions For 07-08 GSXR 1000 Oil Line Extension Blocks S1007-OLEB-KIT



2-Oil Line Extension Block
2-O-Rings
4-Allen head bolts M6x20



Oil cooler removed from bike for clarity



Cut bracket at engine mount below radiator

Retain Stock Oil Cooler with Sidewinder!

1. Remove side fairings.
2. Drain oil.
3. Remove oil cooler from bracket on radiator, by removing bolts above and below oil cooler.
4. Cut bracket as shown in bottom center picture, and remove bracket from engine.
5. Unbolt oil cooler lines from oil cooler, leave lines on engine to keep oil from exiting lines.
6. Bolt extension blocks to oil cooler, make sure factory o-ring is in place (**do not over tighten**).
7. Apply a small amount of new engine oil to supplied o-ring to promote a good seal, and install factory lines to extension blocks (**do not over tighten**).
8. Refill with fresh oil.
9. Reinstall oil cooler to mounting bracket attached to radiator (lower part of bracket removed for use with sidewinder).
10. Install pipe and reinstall bodywork.

Brock's Performance Products are designed for Closed-Course Race Track use ONLY.

Brock's Performance Products policies and warranty information: www.BrocksPerformance.com

For additional information: Check our [Information Forum](http://www.BrocksPerformance.com) at www.BrocksPerformance.com

E-mail advice@BrocksPerformance.com or call the Order Line 937-912-0054.