



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

HONDA GROM (2014) ALIEN HEAD 2 / SHORTMEG 2 FULL EXHAUST INSTALLATION INSTRUCTIONS

Check Package Contents: The Alien Head 2™ or ShortMeg 2™ system package contents include:

1. One Header Mounting Flange
2. One Header
3. One Alien Head 2™ or ShortMeg 2™ Muffler
4. One Muffler Mounting Bracket
5. Package Containing Springs, Spring-puller, and Mounting Hardware

If any parts are missing, please contact Brock's Performance.

Remove the Stock Exhaust System: *Be sure the bike is completely cool before starting the installation.* Remove the muffler heat shield bolt (1) and slide shield forward to release. Loosen the exhaust clamp (2) that secures the muffler to header connection. Remove the two muffler-mount bolts (3 & 4) and carefully remove the muffler. Remove the bolt (5) holding the rear of the header. Support the stock header and remove the header nuts (6 & 7) to completely remove header. **Note:** *The stock exhaust gasket will be reused, but inspect and replace if necessary.*

Install Muffler Mounting Bracket: Remove the two bolts (8 & 9) holding the brake reservoir to the rear set. Position the bracket on the outside of the reservoir and reinstall the stock bolts (10 ft-lb.)

Install the Brock's Performance Exhaust System: Using the supplied nuts (10 & 11), install the header-mounting flange. Do not over tighten; max recommended torque (10 ft-lb.) Install the header and attach spring from flange to header. Install the muffler onto the header and use the supplied hardware to secure to the muffler-mounting bracket (12) loosely. Attach the spring from the muffler to header and adjust the system by hand as required to ensure proper clearance. Tighten the muffler-mounting bolt securely to the bracket (10 ft-lb.)

Check, Clean, Ride: Before starting the motorcycle check for proper clearance between all components (suspension, bodywork, engine, etc.) Wipe the entire exhaust system with rubbing alcohol to remove any oil/fingerprints prior to starting. Enjoy your new Brock's Performance exhaust system.



All Brock's Performance products are designed for closed-course racetrack use ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions: www.BrocksPerformance.com
> About Us > Terms and Conditions

For Questions and Comments: www.BrocksPerformance.com > Customer Service > Contact Us
or call the Tech Line 937-912-0054