



[Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062](#)

CT SERIES™ NOISE REDUCTION PLUG INSTALLATION INSTRUCTIONS

The Noise Reduction Plug (NRP) for Brock's Performance CT Series™ titanium exhaust systems are used to reduce the noise level of the exhaust system with minimal effect on performance. Our Noise Reduction Plugs are easily too installed/uninstall. Also, due to the free flow exhaust design, no map changes are required.

Check Package Contents:

The Package Contents Include:

1. One (1) Noise Reduction Plug

If your package contents differ, please contact Brock's Performance at 937-912-0054.

Instructions:

Caution: Exhaust components will be HOT after use. Allow time to cool before installation or removal.

1. Remove springs from muffler.
2. Remove muffler mounting bolt.
3. Slide muffler off the pipe
4. Insert the NRP into the pipe (Fig 1 & 2)
5. Reinstall the muffler
6. Reinstall the muffler mounting bolt
7. Reinstall the springs
8. For dual systems repeat steps 1 through 7 for the other side.



Fig 1



Fig 2

ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:

BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions

For Questions and Comments:

BrocksPerformance.com > Brock's Support > Customer Service > Contact us or call 937-912-0054