



[Brock's Performance](#) • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

CALIPER DELETE SPACERS PRODUCT INFORMATION

Caliper delete spacers are designed to keep the front radial mount strap brackets in proper alignment after removing a caliper and rotor. Removal of a front caliper and rotor will reduce weight and help showcase the look of the front wheel.

Package Contents:

Caliper Delete Spacers shown:

1. Two (2) Black Anodized Spacers
2. One (1) Product Information Page



Installation Notes:

WARNING: Removing any portion of the braking system will increase stopping distance and reduce braking efficiency. Exercise caution following this modification to avoid personal injury/death or damage to the motorcycle.

- Install Caliper Delete Spacers using the OEM caliper bolts (or the replacement caliper bolts supplied with a Brock's Performance Front End Lowering Kit purchase).
- Torque caliper bolts to OEM torque spec (refer to OEM service manual).
- Caliper Delete Spacers should be installed on the same side as your rear brake (remaining front brake should be diagonal from the rear brake).
- After removing the front caliper, cap all open hydraulic ports and lines.
- Refer to the OEM service manual for proper brake bleeding procedure.

For additional support please refer to the OEM service manuals. They can be found here:
[BrocksPerformance.com](#) > [Brock's Support](#) > [Installation Instructions](#) > [Factory Service Manuals](#)

ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:
[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Terms and Conditions](#)

For Questions and Comments:
[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Contact Us](#) or call 937-912-0054