



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

PAIR BLOCK OFF PLATES (P/N: 280156, 280169 & 280182) PRODUCT INFORMATION

PAIR Block Off Plates are used to block the airports on the cylinder head cover. Blocking the PAIR system prevents unwanted air from entering the exhaust stream, which can decrease exhaust "popping" and is required for a proper vehicle tune.

Package Contents:

PAIR Block Off Plates shown:

1. Two (2) Block Off Plates
(Plates may differ from image)
2. Four (4) Stainless Steel Bolts
3. One (1) Black Airbox Plug
4. One (1) Red Airbox Plug
(ZX-14R applications only)
5. Product Information Page



If your package contents differ, please contact Brock's Performance at 937-912-0054.

Installation Notes:

Note: Removal of the PAIR Valve Solenoid may cause a check engine light on some models. An ECU flash or bypass plug will be required to turn the light off.

- Refer to your factory service manual for OEM PAIR Cap and PAIR Valve Solenoid removal.
- Installs in place of the OEM PAIR caps.
- Remove two screws and four reed valves from each reed plate (Figure 1).
- Inspect reed plates for any damage around outside gasket area. Replace as needed.
- Install Block Off Plates and reed plates using supplied Stainless Steel Bolts. Torque to 7.5 lb.-ft (10 N·m).
- Install Airbox Plug to plug the airbox (not required the Ninja H2).

FIG 1



All Brock's Performance products are designed for closed-course racetrack use ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions: www.BrocksPerformance.com
> About Us > Terms and Conditions

For Questions and Comments: www.BrocksPerformance.com > Customer Service > Contact Us
or call the Tech Line 937-912-0054