Document ID: 996564



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

## HARLEY-DAVIDSON® TOURING (14-18) S&S STEALTH AIR CLEANER KIT INSTALLATION INSTRUCTIONS

The spacer kit is designed to allow the use of the OEM air cleaner cover on Harley-Davidson Touring models in conjunction with the S&S Stealth Air Cleaner Kit

## **Check Package Contents:**

The Package Contents Include:

- 1. One (1) Spacer
- 2. One (1) Washer
- 3. One (1) Bolt

If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional installation support please refer to the OEM service manual.



## **Instructions:**

- The supplied spacer kit (Fig 1) will be used in place of the 5/16" button head screw (Fig 2) included with the S&S Stealth Air Cleaner Kit.
- Place the supplied washer onto the bolt.
- Insert the bolt and washer through the front side of the OEM air cleaner cover.
- Place the spacer over the bolt on the backside of the OEM air cleaner cover.
- Apply blue threadlocker to the bolt threads.
- Install the air cleaner cover and spacer kit as an assembly onto the plastic top filter plate and torque to 10 lb-ft (13.5 N·m)



## ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:

BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions

For Ouestions and Comments:

BrocksPerformance.com > Brock's Support > Customer Service > Contact us or call 937-912-0054