



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

KAWASAKI ZX-14/R (06-19) STEERING DAMPER KIT INSTALLATION INSTRUCTIONS

The Steering Damper Kit for the Kawasaki ZX-14/R allows for installation of a hydraulic shock to prohibit vibration in the steering neck.

Check Package Contents:

The Package Contents Include:

1. One (1) Ohlins Damper
2. One (1) Steering Stem Bracket Assembly
3. One (1) Master Cylinder Bracket
4. One (1) Hardware Kit



If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional installation support please refer to the OEM service manual.

Instructions:

1. Support the bike using a wheel stand or lift.
2. Remove the OEM fuel tank bolt leaving the spacer. (Fig 1)
3. Install the Steering Stem Bracket Assembly and secure. Torque mounting bolt to 9 lb-ft (12 N·m). (Fig 2)
4. Remove two (2) bolts securing the OEM master cylinder bracket.

Note: The OEM master cylinder bracket has an "up" arrow on the clamp and a dimple is located on the handlebar surface for proper location.

5. Install the Master Cylinder Bracket and secure. Torque mounting bolts to 9 lb-ft (12 N·m). (Fig 3)
6. Install the Ohlins Damper and secure. Torque mounting bolts to 13 lb-ft (17.2 N·m).
7. Adjust the position of the Ohlins Damper. Torque clamp bolts to 30 lb-in (3.4 N·m). (Fig 4)

Note: The mounting clamp will be approximately 1.75" (44.5 mm) from the end (Fig 4).

8. Inspect damper clearance from steering lock to lock. If any binding or obstruction occurs, loosen clamp bolts and readjust.



ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:

BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions

For Questions and Comments:

BrocksPerformance.com > Brock's Support > Customer Service > Contact us or call 937-912-0054