



[Brock's Performance](#) • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

SUZUKI GSX-R1000/R (17-19) 'LOWER BRACKET COVER' TRIM INSTRUCTIONS

When using Brock's Performance [Front End Lowering Kit](#) on the GSX-R1000/R trimming the 'lower bracket cover' is required to obtain proper clearance for the Front End Lowering Strap.

Installation Notes:

For additional installation support please refer to the OEM service manual.

- Remove two (2) bolts securing the lower bracket cover. Remove cover.
- Apply painters tape following the dotted cut lines. (Fig 1)
- Using a coping saw (or tool of your choice) carefully cut along the marked areas.
- Carefully smooth the cut edges, using a rotary tool w/drum sander, fine file, or sandpaper.
- A modified lower bracket cover is shown. (Fig 2)
- Reinstall the modified lower bracket cover and check for proper clearance around the Front End Lowering Strap.

FIG 1



FIG 2



ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:

[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Terms and Conditions](#)

For Questions and Comments:

[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Contact us](#) or call 937-912-0054