Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

NINJA H2 (15-26) & ZX-10R (11-15) STEERING DAMPER RISER KIT INSTALLATION INSTRUCTIONS

The Steering Damper Riser kit is designed to provide clearance for the OEM steering damper when raising the fork tubes up to 1" (25.4 mm) through the triple tree to lower the front end.

Check Package Contents:

The Package Contents Include:

1. One (1) Short Spacer
2. One (1) Tall Spacer
3. Two (2) Button Head Bolts

If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional installation support please refer to the OEM service manual.

Instructions:

1. Support the bike using a wheel stand or lift.
2. Unplug the steering damper connector.
3. Remove two bolts securing the steering damper (T-40 security bit is required).
4. Assemble the supplied short and tall spacers along with the OEM washers and collar in place.
5. Secure the steering damper to the bike using the supplied button head bolts. Torque to 97 lb-in (11 N·m).
6. Reconnect the steering damper connector.
7. Verify the steering damper is free to travel from steering lock to lock.

ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!
For more information on Brock's Performance Warranty and Terms and Conditions:
BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions
For Questions and Comments:
BrocksPerformance.com > Brock's Support > Customer Service > Contact us or call 937-912-0054