Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

NINJA H2 (15-26) MIRROR BLOCK OFF PLATES PRODUCT INFORMATION

Mirror Block Off Plates are designed to replace the OEM side view mirrors. Removal of the OEM side view mirrors reduces weight and aerodynamic drag. Mirror Block Off Plates are used to cover the holes left behind.

Package Contents:

The package contents include:

1. One (1) Left Mirror Block Off Plate
2. One (1) Right Mirror Block Off Plate
3. Four (4) Black Aluminum Screws

If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional installation support please refer to the OEM service manual.

Installation Notes:

NOTE: *This product is* ***NOT DOT*** *approved for street use.*

- Remove left and right side inner covers to access turn signal wiring harness.
- Disconnect OEM turn signals.
- Remove OEM side view mirrors.
- Install Mirror Block Off Plates using the supplied black aluminum screws.
- Torque black aluminum screws to 72 lb-ib. (8 N·m).
- Re-install inner covers.

ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:
BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions
For Questions and Comments:
BrocksPerformance.com > Brock's Support > Customer Service > Contact Us or call 937-912-0054