Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

Z H2 (20-26), H2 (15-26), & ZX-10R (16-26) WHEEL SPEED SENSOR EXTENSION HARNESS PRODUCT INFORMATION

For extended bike applications, this Wheel Speed Sensor (WSS) Extension Harness simply plugs in-line with the OEM wheel speed sensor. No cutting or splicing required. Functions with the OEM ABS and TCS.

Package Contents:

WSS Extension Harness shown:

1. One (1) WSS Extension Harness

If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional support please refer to the OEM service manual.

Installation Notes:

Caution: Do not drop or hit the OEM WSS as damage may occur.

- Remove the fuel tank to access WSS connector.
- Plug the WSS extension harness in-line with the OEM WSS wiring.
- Route wiring along the swingarm. Check for a secure fit and clearance around any moving parts/exhaust.
- Inspect WSS rotor for any damage or debris. Replace or clean as needed.



ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:
BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions
For Questions and Comments:
BrocksPerformance.com > Brock's Support > Customer Service > Contact Us or call 937-912-0054