



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

## HAYABUSA (99-07) PAIR VALVE REMOVAL KIT INSTALLATION INSTRUCTIONS

The block off plates for your exhaust system purchase is used to block off the flow of fresh air into the exhaust system preventing 'deceleration pop'. Blocking of the PAIR system is also required for proper fuel tuning of the bike.

### Check Package Contents:

#### The Package Contents Include:

1. Four (4) Block Off Plates
2. Eight (8) Flange Nuts
3. One (1) Block Off Cap
4. One (1) Vacuum Cap
5. Four (4) O-Rings



If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional installation support refer to the OEM service manual.



### Instructions:

1. Support the bike using a wheel stand or lift.
2. Remove body panels and prop up the fuel tank.
3. Disconnect PAIR Tubes from exhaust ports and clean surface (Fig 1).
4. Disconnect large PAIR Hose from Air Box and seal with supplied Block Off Cap (Fig 2).
5. Disconnect small PAIR Hose from throttle body #4, seal with supplied Vacuum Plug (Fig 3).
6. Unbolt PAIR Valve Assembly from mounting base. The mounting base will remain on the engine (Fig 4).
7. Install Brocks Performance Block Off Plates/O-rings and flange nuts. Torque nuts to 7.0 lb-ft (9.5 N·m) (Fig 5).
8. Re-Assemble Bike.



**ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!**

For more information on Brock's Performance Warranty and Terms and Conditions:  
[BrocksPerformance.com](http://BrocksPerformance.com) > [Brock's Support](#) > [Customer Service](#) > [Terms and Conditions](#)

For Questions and Comments:

[BrocksPerformance.com](http://BrocksPerformance.com) > [Brock's Support](#) > [Customer Service](#) > [Contact us](#) or call 937-912-0054