



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

HAYABUSA (99-07) AIRBOX MOD INSTRUCTIONS

For additional installation support please refer to the OEM service manual.

Instructions:

1. Drill a series of ¼" (6 mm) holes around the inside of the air filter locator ridge. Be careful to only pierce the surface. Do not drill to deep (Fig 1).
2. Carefully trim around the inside of the ridge. A large knife with a serrated blade/small hobby saw works well (Fig 2).
3. Remove the inner section of the air box, flapper, etc. (Fig 3).
4. Smooth the inside of the ridge. A Dremel tool or cutter mounted on a Hand Drill works best (Fig 4).
5. Plug the PAIR valve inlet. See [Brock's PAIR Block Off Plates](#) for details.
6. Re-connect or plug the diaphragm hose.
7. Install Air Filter. For maximum airflow/power pair this mod with a [Sprint Filter](#).
8. Load appropriate Power Commander Map for the modified airbox.



ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:

BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions

For Questions and Comments:

BrocksPerformance.com > Brock's Support > Customer Service > Contact us or call 937-912-0054