



[Brock's Performance](#) • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

NOISE REDUCTION PLUG (2.00" & 2.25") INSTALLATION INSTRUCTIONS

Noise Reduction plugs are designed to provide users with an easily removable option for noise reduction with minimal effect on horsepower and sound quality.

Check Package Contents:

The Package Contents Include:

1. One (1) Noise Plug Body
2. Two (2) Clamps
3. Two (2) Bolts

If your package contents differ, please contact Brock's Performance at 937-912-0054.

For additional installation support please refer to the OEM service manual.



Installation Notes:

Caution: Exhaust components will be HOT after use. Allow time to cool before installation or removal.

- Installs to 2.00" or 2.25" select Brocks Performance full exhaust systems and slip-ons.
- Easily installs using a 4 mm Allen wrench.
- The noise reduction plug will sit flush with the muffler outlet. Use a soft-faced mallet to tap into place as needed.
- After installing the noise reduction plug, give it a good pull to check for a secure fit to the muffler.
- The actual decibel reading from the exhaust will vary depending on the bike and modifications.
- **Note:** Due to heat, pressure, and vibration (**notably on the Ninja H2**) noise reduction plug mounting bolts can loosen over time. Periodically check the noise reduction plug for a secure fit.



ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions:

[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Terms and Conditions](#)

For Questions and Comments:

[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Contact us](#) or call 937-912-0054