



[Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062](#)

## BROCK'S PERFORMANCE LOGO PLATE INSTALLATION INSTRUCTIONS

**Brock's Performance logo plates are available in several different colors and two different styles. They are secured using blind rivets to the muffler.**

### Check Package Contents:

#### The Package Contents Include:

1. One (1) Logo Plate
  2. Two (2) Rivets
- \*Part color/style may differ from image*



**If your package contents differ, please contact Brock's Performance at 937-912-0054.**

### Removal Instructions:

1. Support the bike using a wheel stand or lift.
2. Remove the muffler from the bike and place it on a flat work surface.
3. Using a center punch, place an indentation in the center of the rivet head.
4. Using a **#30** (.1285" or 3.25mm) drill bit ([sold separately](#)), drill through the rivet until the drill bit goes all the way through the rivet hole.

**Note:** For best results, drill at a low speed with light pressure. It is also recommended to assure the drill bit is sharp.

5. Remove the old logo plate.

### Installation Instructions:

**High Heat Note:** If installing the logo plate onto a Ti/Sidewinder exhaust system or any other muffler with the baffle packing removed, a special high heat coating (applied if option selected) must be applied to prevent damage to the logo plate.

6. Align the two holes in the new logo plate with the two holes in the muffler.
7. Check the bend in the logo plate to the muffler. Adjust as needed so the plate sits flat on the muffler.
8. Select the proper mandrel (1/8") for the blind rivet tool.
9. Install both rivets to hold the logo plate in place.

**TiWinder Note:** If installing the logo plate onto a TiWinder exhaust system the supplied washers must be used. Place the washers over the rivet heads, on the inside of the muffler, prior to securing the rivets in place.

10. Using the rivet tool, secure the logo plate with the two rivets.
11. Reinstall the muffler.
12. Use isopropyl alcohol and wipe down muffler before starting the bike.



**ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!**

For more information on Brock's Performance Warranty and Terms and Conditions:

**BrocksPerformance.com > Brock's Support > Customer Service > Terms and Conditions**

For Questions and Comments:

**BrocksPerformance.com > Brock's Support > Customer Service > Contact us or call 937-912-0054**