



Brock's Performance Products • 4064 East Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

SLIP-ON MOUNTING INSTRUCTIONS

To install your **Brock's Performance** slip-ons, proceed with the following directions:

1. Remove the stock muffler and stock elbow as per owner's manual.
2. Install elbow onto collector using high temperature silicone sealant on inside of elbow and install springs. We suggest Permatex® Ultra Copper® Maximum Temperature RTV Silicone Gasket Maker.
3. Slide muffler over top of elbow. Use small amount of sealant on the inside of the muffler.
4. Install muffler clamp with rubber or mounting bracket for "GP Style" systems and StreetMeg style megaphones.
5. For high pipe systems, remove both rear passenger foot pegs and use custom bracket provided to mount muffler. Please refer to special mounting instructions to proceed.
6. Enjoy the added performance look and sound of your new Brock's Performance exhaust system!

Brock's Performance Products are designed for Closed-Course Racetrack use ONLY!

For more information, go to www.BrocksPerformance.com; click: Installation Instructions.

If you have questions, you can e-mail us at Advice@BrocksPerformance.com, or call the office at 937-912-0054.

For Brock's Performance Products policies and warranty information, go to www.BrocksPerformance.com; click: Policies.