



[Brock's Performance](#) • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

## KAWASAKI ZX-14 (06-11) PAIR BLOCK-OFF CAP INSTALLATION INSTRUCTIONS

The red cap is used to block off the flow of fresh air into the exhaust system preventing 'deceleration pop' and ram air pressure loss. Blocking the PAIR system is also required for proper fuel tuning of the bike.

For additional installation support please refer to the OEM service manual.



1. Remove right side fairing and locate the PAIR hose underneath the airbox. (Fig 1)
2. Remove PAIR hose from the grommet in the airbox. (Fig 1)
3. Cut the PAIR hose off flat, just below the 45° angle. (Fig 1)
4. Lubricate the cap using WD40 and push the cap into the grommet. (Fig 2)
5. Reinstall hose into the airbox grommet. (Fig 3)
6. Reinstall right side fairing.



**Figure 1. ZX-14 Air Box Hose.**

**Figure 2. Red Plastic Block Off Cap Inserted.**

**Figure 3. Red Block Off Cap Installed.**

**ALL BROCK'S PERFORMANCE PRODUCTS ARE DESIGNED FOR CLOSED-COURSE RACETRACK USE ONLY!**

For more information on Brock's Performance Warranty and Terms and Conditions:

**[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Terms and Conditions](#)**

For Questions and Comments:

**[BrocksPerformance.com](#) > [Brock's Support](#) > [Customer Service](#) > [Contact us](#) or call 937-912-0054**