Material number



AJ3719 ORIGINAL SPRAY CLEANER POL 16N14

Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019	
SECTION 1. PRODUCT AND COMPANY IDENTIFICATION			
Material name	: AJ3719 ORIGINAL SPRAY CLEA	NER POL 16N14	

: 00000000001039615

Manufacturer or supplier's details					
Company	:	Zep Inc.			
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137			
Telephone	:	404-352-1680			

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Transportation Wash

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

GHS Classification

Appearance	Aerosol containing a liquefied gas
Colour	opaque, white
Odour	characteristic

Che Classification	
Flammable aerosols Gases under pressure	: Category 1 : Liquefied gas
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated.

_



AJ3719 ORIGINAL SPRAY CLEANER POL 16N14

Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
Precautionary statements	 Prevention: P210 Keep away from heat, hot surface and other ignition sources. No smoking P211 Do not spray on an open flame of P251 Pressurized container: Do not picture. Storage: P410 + P412 Protect from sunlight. Do temperatures exceeding 50 °C/ 122 °F Disposal: P501 Dispose of contents/container in regulation. 	g. or other ignition source. erce or burn, even after o not expose to

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 5 - < 10
propane	74-98-6	>= 3 - < 5
butane	106-97-8	>= 3 - < 5
Amides, tall-oil fatty, N,N-bis(hydroxyethyl)	68155-20-4	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	 Wash off with soap and water. If skin irritation persists, call a physician. If on clothes, remove clothes. Wash off immediately with plenty of water for at least 15 minutes.
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.
If swallowed	 Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.



Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
	DO NOT induce vomiting unless di physician or poison control center.	
Most important symptoms and effects, both acute and delayed	: Effects may be delayed, symptoms skin irritation. Overexposure may cause mild eye	
Notes to physician	: Treat symptomatically. Symptoms	may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical Water spray jet
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke Silicon oxides Nitrogen oxides (NOx)
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform

_



AJ3719 ORIGINAL SPRAY CLEANER POL 16N14

Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
	respective authorities.	
Methods and materials for containment and cleaning up	 Sweep up or vacuum up spillage a container for disposal. Soak up with inert absorbent mater acid binder, universal binder, sawd 	rial (e.g. sand, silica gel,

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Avoid exposure - obtain special instructions before use. Do not breathe vapours or spray mist. Always replace cap after use.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Keep in a dry, cool and well-ventilated place.
Materials to avoid	: Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
		PEL (particulate)	5 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm	NIOSH REL



/ersion 5.0	Revision	Date 12/03/20	18 Print [Date 09/10/2019
			1,800 mg/m3	1
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL

Personal protective equipment

Respiratory protection	:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection Material Remarks		Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas	
Colour	: opaque, white	
Odour	: characteristic	
Odour Threshold	: No data available	
рН	: Not applicable	
Melting point/freezing point	: No data available	
Boiling point	: Not applicable	
Flash point	: Not applicable	



Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
Evaporation rate	: No data available	
Flammability (solid, gas)	: Extremely flammable aerosol.	
Upper explosion limit	: No data available	
Lower explosion limit	: No data available	
Vapour pressure	: No data available	
Density	: 0.95 g/cm3	
Solubility(ies)		
Water solubility	: dispersible	
Solubility in other solvents	: not determined	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: > 1000 mm2/s (40 °C)	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides Sodium oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects may be delayed, symptoms may include minor eye or skin irritation.



Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
Carcinogenicity:		
IARC	Group 2A: Probably carcinogenic to hu	imans
ACGIH	sodium nitrite No component of this product present equal to 0.1% is identified as a carcino carcinogen by ACGIH.	
OSHA	No component of this product present	
NTP	equal to 0.1% is on OSHA's list of reguning the component of this product present equal to 0.1% is identified as a known by NTP.	at levels greater than or
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg Method: Calculation method	/kg
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg Method: Calculation method	/kg
Components:		
Distillates (petroleum), hyc Acute oral toxicity		
Acute inhalation toxicity	: LC50 Rat: > 4.6 mg/l Exposure time: 6 h	
Acute dermal toxicity	: LD50 Rat: > 2,000 mg/kg	
Amides, tall-oil fatty, N,N-b Acute oral toxicity	bis(hydroxyethyl): : LD50 Oral Rabbit: 2,200 mg/kg	
	LD50 Oral Mouse: 3,300 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: 12,200 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: May cause skin irr	itation and/or dermatitis.	
Serious eye damage/eye irritati	on	
Product:		
Remarks: Vapours may caus	se irritation to the eyes, respiratory system	and the skin.

Respiratory or skin sensitisation

No data available



		T
Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
Further information		
Product:		
Remarks: No data available		

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available	
Persistence and degradability	
No data available Bioaccumulative potential	
<u>Components:</u> butane : Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available <u>Product:</u>	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A



Version 5.0	Revision Date 12/03/2018	Print Date 09/10/2019
	+ B).	
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful aquatic life with long lasting effects.	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.



Version 5.0	
VEISION 5.0	

Revision Date 12/03/2018

Print Date 09/10/2019

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Gases under pressure
SARA 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	
	WARNING: This product can expose you to chemicals including 2,2'-iminodiethanol, ethylbenzene, benzene, naphthalene, which is/are known to the State of California to cause cancer, and methanol, toluene, benzene, which is/are known to the State of California to cause birth defects or other

www.P65Warnings.ca.gov.

reproductive harm. For more information go to

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION




Version 5.0

Revision Date 12/03/2018

Print Date 09/10/2019

Further information



HMIS III:

HEALTH	1
FLAMMABILITY	4
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

OSHA - GHS Label Information:

Signal word Hazard statements Precautionary statements

Hazard pictograms



Danger:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	5.0
Revision Date:	12/03/2018
Print Date:	09/10/2019

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal[™], and a number of private labeled brands.

^{2 =} Moderate, 3 = High 4 = Extreme, * = Chronic