



# **RU-GLYDE<sup>®</sup>**

## **Tire Mounting & Rubber Lubricant**



**READY TO USE!**

Lubrication is an essential part of tire mounting and dismounting service. Always lubricate with RuGLYDE<sup>®</sup> to protect against bead damage and to help seat tire beads properly on the rim. Will not cause rust or cause tires to slip after mounting and balancing.

### **MOUNT AND DISMOUNT TIRES**

#### **Tubeless Tires**

**MOUNTING:** Clean sealing areas by applying RuGLYDE<sup>®</sup> with brush and wipe off excess. Apply RuGLYDE<sup>®</sup> with applicator to tire beads and both bead edges. Follow tire manufacturers' recommendations for inflation pressure.

**DISMOUNTING:** After breaking bead, apply RuGLYDE<sup>®</sup> to bead before dismounting to save time and effort. Prevents damage to sealing areas.  
**IMPORTANT:** Always mount and dismount tires from the narrow side of the rim.

#### **Tires and Tubes**

**MOUNTING:** Lubricate tires and tubes so tube will slip, not stretch, into place. Put tube in tire and partially inflate. Lubricate around tire on both sides to 2" above bead. Also apply on rim side of tube.

**DISMOUNTING:** Apply RuGLYDE<sup>®</sup> to both sides of tire along edge of rim. Allow to penetrate for a few minutes, then dismount.

### **LUBRICATE RUBBER PARTS**

Stops rubber squeaks. Safest and longest-lasting lubricant for rubber bushings, shock absorber and stabilizer linkage, shackles, grommets, insulating strips or pads, and other rubber parts. For best results, wipe off dirt before applying. Apply with any suitable oiler, spray gun, brush, or applicator.

### **CLEANS & RENEWS**

Restores new look to floor mats, tires, upholstery, and other rubber, leather, or plastic parts. Renews appearance of any color materials.

### **DIRECTIONS**

Remove loose dirt. Apply RuGLYDE<sup>®</sup> with brush, cloth or sponge. Rub until all dirt is loosened. Wipe off with cloth (preferable) or flush with water. To clean and preserve leather and vinyl upholstery, use sponge saturated with RuGLYDE<sup>®</sup>. Wipe off with damp cloth. For rough upholstery, use stiff bristle brush.

### **WARNING!**

**CAUSES EYE IRRITATION.** Avoid contact with eyes. Wash hands thoroughly after use.

**FIRST AID:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call physician or poison control immediately.

#### **INGREDIENTS:**

	<b>CAS#</b>	<b>WT. %</b>
Water	7732-18-5	85-90%
Potassium Vegetable Oil Soap	Not Assigned	5-15%
Ethylene Glycol	107-21-1	1-5%



***The #1 Choice in Specialty Lubricants***

A Product of **AGS Company** • Muskegon, MI 49443 USA  
Made in the U.S.A. [www.agscompany.com](http://www.agscompany.com)